

Certificate of Compliance

Certificate Number:

UL-US-L511334-11-
71100202-8

Report Reference:

E511334-20200117

Issue Date:

2024-11-12

Issued to:

Shanghai Chipanalog Microelectronics Co Ltd
2nd floor Block C, Beidou Industrial Park of Xihongqiao,NO.599
Gaojing Road,Qingpu District Shanghai 201702
China

This certificate confirms that representative samples of:

FPPT2 - Nonoptical Isolating Devices - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1577, Edition 5, Issue Date 2014-04-25, Revision Date 2023-07-06

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink that reads 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
CA-IS-3762HB-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3105W	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3105W-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3115AW	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3115AW-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3115BW	Single protection non-optical isolators at 2500 Vac isolation voltage
CA-IS3115BW-Q1	Single protection non-optical isolators at 2500 Vac isolation voltage
CA-IS3211SBG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211SBG-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211SCG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211SCG-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VBG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211VBG-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VBJ	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211VBJ-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VBU	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3211VCG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211VCG-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VCJ	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211VCJ-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VCU	Single protection non-optical isolators at 5700 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3211VCU-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215LNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215LNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215NEW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215NEW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215NNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215NNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215SEW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215SEW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215SNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215SNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215VNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215VNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216NEW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216NEW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216NNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216NNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216SEW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216SEW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216SNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216SNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221AN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3221AN-Q1	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3221AW	Single protection non-optical isolators at 5700 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3221AW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221BK	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221BK-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3221BN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3221BN-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3221BW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221BW-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3221CK	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221CK-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3221CN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3221CN-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3221CW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221CW-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3222BK	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3222BK-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3222BN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3222BN-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3222BW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3222BW-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3222CK	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3222CK-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3222CN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3222CN-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3222CW	Single protection non-optical isolators at 5700 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3222CW-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3710HG	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3710HG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3710HS	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3710HS-Q1	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3710LG	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3710LG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3710LS	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3710LS-Q1	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3720HG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720HG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3720HS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3720HS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3720HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720LG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720LG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3720LS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3720LS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3720LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720VLS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721HG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721HG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3721HS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721HS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721LG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721LG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3721LS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721LS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722HG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722HG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3722HS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3722HS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3722HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722LG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722LG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3722LS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3722LS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3722LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3730HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3730HN	Single protection non-optical isolator providing 3750 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3730HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3730HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3730LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3730LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3730LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3730LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3731HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3731HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3731HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3731HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3731LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3731LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3731LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3731LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3735HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3735HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3735LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3735LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3740HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3740HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3740LN	Single protection non-optical isolator providing 3750 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3740LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740VLN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3741HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3741HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3741HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3741HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3741LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3741LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3741LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3741LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3742HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3742HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3742HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3742HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3742LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3742LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3742LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3742LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3745HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3745HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3745LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3745LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3750HN	Single protection non-optical isolator providing 3750 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3750HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3750LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3750LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3751HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3751HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3751LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3751LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3752HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3752HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3752LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3752LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3755HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3755HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3755LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3755LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3760HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3760HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3760HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3760HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3760LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3760LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3760LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3760LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3761HB	Single protection non-optical isolators at 3750 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3761HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3761HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3761HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3761LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3761LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3761LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3761LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3762HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3762HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3762HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3762HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3762LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3762LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3762LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3762LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3763HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3763HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3763HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3763HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3763LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3763LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3763LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3763LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3820HG	Single protection non-optical isolator providing 5700 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3820HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3820HWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3820LG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3820LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3820LWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3821HG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3821HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3821HWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3821LG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3821LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3821LWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3822HG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3822HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3822HWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3822LG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3822LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3822LWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3830HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3830HWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3830LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3830LWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3831HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3831HWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3831LW	Single protection non-optical isolator providing 5700 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3831LWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3840HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3840HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3840LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3840LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3841HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3841HWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3841LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3841LWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3842HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3842HWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3842LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3842LWW	Single protection non-optical isolator providing 7500 Vac isolation
CA-IS3860HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3860HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3860LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3860LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3861HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3861HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3861LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3861LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3862HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3862HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3862LW	Single protection non-optical isolator providing 5700 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511334-11-71100202-8
Report reference E511334-20200117
Date 2024-11-12

CA-IS3862LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3863HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3863HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3863LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3863LWW	Single protection non-optical isolator providing 5700 Vac isolation
CS817x20HS	Single protection non-optical isolator providing 3000 Vac isolation
CS817x20LS	Single protection non-optical isolator providing 3000 Vac isolation
CS817x22HS	Single protection non-optical isolator providing 3000 Vac isolation
CS817x22LS	Single protection non-optical isolator providing 3000 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-L511334-21-
71100202-7

Report Reference:

E511334-20200117

Issue Date:

2024-11-12

Issued to:

Shanghai Chipanalog Microelectronics Co Ltd
2nd floor Block C, Beidou Industrial Park of Xihongqiao,NO.599
Gaojing Road,Qingpu District Shanghai 201702
China

This certificate confirms that representative samples of:

**FPPT8 - Nonoptical Isolating Devices Certified for Canada -
Component**

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

**CSA Component Acceptance Service Notice No. 5A, Issue Date:
1998-01-23**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
CA-IS-3762HB-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3105W	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3105W-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3115AW	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3115AW-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3115BW	Single protection non-optical isolators at 2500 Vac isolation voltage
CA-IS3115BW-Q1	Single protection non-optical isolators at 2500 Vac isolation voltage
CA-IS3211SBG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211SBG-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211SCG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211SCG-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VBG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211VBG-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VBJ	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211VBJ-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VBU	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3211VCG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211VCG-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VCJ	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3211VCJ-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3211VCU	Single protection non-optical isolators at 5700 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3211VCU-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215LNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215LNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215NEW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215NEW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215NNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215NNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215SEW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215SEW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215SNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215SNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215VNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3215VNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216NEW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216NEW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216NNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216NNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216SEW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216SEW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216SNW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3216SNW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221AN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3221AN-Q1	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3221AW	Single protection non-optical isolators at 5700 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3221AW-Q1	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221BK	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221BK-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3221BN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3221BN-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3221BW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221BW-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3221CK	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221CK-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3221CN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3221CN-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3221CW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3221CW-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3222BK	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3222BK-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3222BN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3222BN-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3222BW	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3222BW-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3222CK	Single protection non-optical isolators at 5700 Vac isolation voltage
CA-IS3222CK-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3222CN	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3222CN-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3222CW	Single protection non-optical isolators at 5700 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3222CW-Q1	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3710HG	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3710HG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3710HS	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3710HS-Q1	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3710LG	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3710LG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3710LS	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3710LS-Q1	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3720HG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720HG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3720HS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3720HS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3720HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720LG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720LG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3720LS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3720LS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3720LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3720VLS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721HG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721HG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3721HS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721HS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721LG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721LG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3721LS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721LS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3721LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3721LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722HG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722HG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3722HS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3722HS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3722HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722LG	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722LG-Q1	Single protection non-optical isolators at 5000 Vac isolation voltage
CA-IS3722LS	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3722LS-Q1	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3722LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3722LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3730HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3730HN	Single protection non-optical isolator providing 3750 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3730HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3730HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3730LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3730LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3730LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3730LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3731HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3731HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3731HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3731HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3731LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3731LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3731LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3731LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3735HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3735HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3735LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3735LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3740HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3740HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3740LN	Single protection non-optical isolator providing 3750 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3740LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3740VLN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3741HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3741HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3741HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3741HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3741LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3741LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3741LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3741LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3742HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3742HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3742HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3742HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3742LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3742LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3742LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3742LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3745HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3745HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3745LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3745LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3750HN	Single protection non-optical isolator providing 3750 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3750HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3750LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3750LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3751HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3751HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3751LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3751LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3752HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3752HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3752LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3752LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3755HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3755HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3755LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3755LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3760HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3760HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3760HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3760HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3760LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3760LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3760LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3760LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3761HB	Single protection non-optical isolators at 3750 Vac isolation voltage



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3761HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3761HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3761HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3761LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3761LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3761LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3761LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3762HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3762HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3762HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3762HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3762LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3762LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3762LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3762LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3763HB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3763HN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3763HW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3763HW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3763LB	Single protection non-optical isolators at 3750 Vac isolation voltage
CA-IS3763LN	Single protection non-optical isolator providing 3750 Vac isolation
CA-IS3763LW	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3763LW-Q1	Single protection non-optical isolator providing 5000 Vac isolation
CA-IS3820HG	Single protection non-optical isolator providing 5700 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3820HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3820LG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3820LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3821HG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3821HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3821LG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3821LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3822HG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3822HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3822LG	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3822LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3830HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3830HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3830LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3830LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3831HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3831LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3840HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3840HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3840LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3840LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3841HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3841LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3842HW	Single protection non-optical isolator providing 5700 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L511334-21-71100202-7
Report reference E511334-20200117
Date 2024-11-12

CA-IS3842LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3860HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3860HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3860LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3860LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3861HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3861HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3861LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3861LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3862HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3862HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3862LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3862LWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3863HW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3863HWW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3863LW	Single protection non-optical isolator providing 5700 Vac isolation
CA-IS3863LWW	Single protection non-optical isolator providing 5700 Vac isolation
CS817x20HS	Single protection non-optical isolator providing 3000 Vac isolation
CS817x20LS	Single protection non-optical isolator providing 3000 Vac isolation
CS817x22HS	Single protection non-optical isolator providing 3000 Vac isolation
CS817x22LS	Single protection non-optical isolator providing 3000 Vac isolation



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.